

EXPLORER ANALYTICAL – EX224/AD – 30061977

SPECIFICATION

Maximum Capacity	220 g
Readability	0.1 mg
Pan Size	3.5 in (90 mm)
Internal Calibration	AutoCal™ - Automatic
Draftshield	Included
Auto Door	Included
Auxiliary Display Model	Available as an Accessory
Battery Life	Not applicable

Communication	Ethernet (Available as an Accessory); USB (Included); RS232 (Included)
Dimensions	15.5 in x 13.8 in x 9.1 in (393 mm x 350 mm x 230 mm) (LxHxW)
Display	Full-color 5.7 in VGA, touch screen
In-Use Cover	Included
Legal for Trade	Not Applicable
Linearity ±	0.0002 g
Minimum Weight (USP, 0.1%, typical)	0.16 g
Net Weight	15.2 lb (6.9 kg)
Pan Construction	Stainless Steel

Power	AC Adapter (Included)
Repeatability, typical	0.0001 g
Stabilization Time	2 s
Tare Range	To capacity by subtraction
Units of Measurement	Singapore Tael; Ounce Troy; Pennyweight; Grain; Kilogram; Tical; Custom; Milligram; Momme; Newton; Baht; Taiwan Tael; Gram; Hong Kong Tael; Pound; Tola; Mesghal; Carat; Ounce
Working Environment	50°F – 86°F, 85%RH, non-condensing (10°C – 30°C, 85%RH, non-condensing)
