## EXPLORER PRECISION - EX223/E - 30061979 SPECIFICATIONS

Maximum Capacity	220 g
Readability	1 mg
Pan Size	5.1 in (130 mm)
Internal Calibration	Not applicable
Draftshield	Included
Auxiliary Display Model	Available as an Accessory
Battery Life	Not applicable
Communication	Ethernet (Available as an Accessory); USB (Included); RS232 (Included)

Dimensions	15.5 in x 13.8 in x 9.1 in (393 mm x 350 mm x 230 mm) (LxHxW)
Display	Full-color 5.7 in VGA, touch screen
In-Use Cover	Included
Legal for Trade	Not Applicable
Linearity ±	$0.002~\mathrm{g}$
Minimum Weight (USP, 0.1%, typical)	1.6 g
Net Weight	15.2 lb (6.9 kg)
Pan Construction	Stainless Steel
Power	AC Adapter (Included)

Repeatability, typical	0.001 g
Stabilization Time	1 s
Tare Range	To capacity by subtraction
Units of Measurement	Singapore Tael; Ounce Troy; Pennyweight; Grain; Kilogram; Tical; Custom; Milligram; Momme; Newton; Baht; Taiwa Tael; Gram; Hong Kong Tael; Pound; Tola; Mesghal; Carat; Ounce
Working Environment	50°F – 86°F, 85%RH, non-condensing (10°C – 30°C, 85%RH, non-condensing)