

EXPLORER PRECISION EX6202/E – 30061983

SPECIFICATIONS

Maximum Capacity	6,200 g
Readability	0.01 g
Pan Size	7.5 in x 8 in (190 mm x 200 mm)
Internal Calibration	Not applicable
Draftshield	—
Auxiliary Display Model	Available as an Accessory
Battery Life	Not applicable
Communication	Ethernet (Available as an Accessory); USB (Included); RS232 (Included)

Dimensions	15.5 in x 3.9 in x 9.1 in (393 mm x 98 mm x 230 mm) (LxHxW)
Display	Full-color 5.7 in VGA, touch screen
In-Use Cover	Included
Legal for Trade	Not Applicable
Linearity \pm	0.02 g
Minimum Weight (USP, 0.1%, typical)	16 g
Net Weight	11 lb (5 kg)
Pan Construction	Stainless Steel
Power	AC Adapter (Included)

Repeatability, typical	0.01 g
Stabilization Time	1 s
Tare Range	To capacity by subtraction
Units of Measurement	Singapore Tael; Ounce Troy; Pennyweight; Grain; Kilogram; Tical; Custom; Milligram; Momme; Newton; Baht; Taiwan Tael; Gram; Hong Kong Tael; Pound; Tola; Mesghal; Carat; Ounce
Working Environment	50°F – 86°F, 85%RH, non-condensing (10°C – 30°C, 85%RH, non-condensing)
