## EXPLORER SEMI MICRO – EX225DM/AD - 30139518 SPECIFICATIONS

Maximum Capacity	120 g/220 g
Readability	0.01 mg; 0.1 mg
Readability (Certified)	1 mg
Pan Size	3.14 in (80 mm)
Internal Calibration	AutoCal™ - Automatic
Draftshield	Included
Auto Door	Included
Auxiliary Display Model	Available as an Accessory

Battery Life	Not Applicable
Built-in lonizer	Yes
Communication	Ethernet (Available as an Accessory); USB (Included); RS232 (Included); USB Host
Dimensions	15.5 in x 13.8 in x 9.1 in (393 mm x 350 mm x 230 mm) (LxHxW)
Display	Full-color 5.7 in VGA, touch screen
In-Use Cover	Included
Legal for Trade	EC Type Approved
Linearity ±	0.1 mg
Minimum Weight (USP, 0.1%, typical)	20 mg
Net Weight	7.5 kg

Pan Construction	Stainless Steel
Power	AC Adapter (Included)
Repeatability, typical	0.015 mg
Stabilization Time	8 s
Tare Range	To capacity by subtraction
Units of Measurement	Milligram; Gram; Carat
Working Environment	50°F – 86°F, 85%RH, non-condensing (10°C – 30°C, 85%RH, non-condensing)