

PIONEER ANALYTICAL – PX124 – 30429803

SPECIFICATIONS

Maximum Capacity	120 g
Readability	0.1 mg
Pan Size	90 mm
Internal Calibration	InCal™ - Semi Automatic
Draftshield	Included
Auxiliary Display Model	Available as an Accessory
Battery Life	Not applicable
Communication	USB; RS232

Dimensions	321 mm x 309 mm x 209 mm (LxHxW)
Display	2-Line LCD with Backlight
In-Use Cover	Included
Legal for Trade	No
Linearity \pm	0.0002 g
Minimum Weight (USP, 0.1%, typical)	200 mg
Net Weight	10 lb (4.5 kg)
Pan Construction	Stainless Steel
Power	AC Adapter (Included)

Repeatability, typical	0.0001 g
Stabilization Time	3 s
Tare Range	To capacity by subtraction
Units of Measurement	Singapore Tael; Pennyweight; Ounce Troy; Kilogram; Grain; Tical; Custom; Milligram; Newton; Momme; Taiwan Tael; Baht; Gram; Hong Kong Tael; Pound; Tola; Mesghal; Ounce; Carat
Working Environment	operability guaranteed between 41°F and 104°F; 50°F – 86°F, 80%RH, non-condensing (operability guaranteed between 5° 40°C; 10°C – 30°C, 80%RH, non-condensing)
